# Labthink®

**C650B Headspace Gas Analyzer** is featured with handheld design and equipped with high precision sensors and air pump supplied by globally well-known manufacturers. It can provide accurate and fast evaluation of the volume of oxygen and carbon dioxide (with optional  $CO_2$  sensor) in sealed packages, bottles and cans, etc. Because of its portable design, the instrument can be used to measure the volume and proportion of oxygen and carbon dioxide on production lines, in warehouses or in laboratories, to serve as a guide for production.

### **Product Features** Note1

- Handheld and portable design, easy-to-operate with one hand, suitable for tests on production line
- Auto shutdown for energy saving
- One-button calibration, simple and efficient
- Components and parts are supplied by global well-known manufacturers, which guarantee stable performance of the instrument
- Protective cover for sampling probe to ensure the safety of the operator
- Embedded gas sensors for accurate analysis of the gas contents inside flexible or rigid packages
- Embedded pressure sensor for accurate determination of the vacuum degree inside the package
- CO<sub>2</sub> sensor uses NDIR technology, patented solid state LED, detector and gold-plated optic components
- The sensors are supplied by global well-known manufacturers, have ultra-high precision, low fault rate and long service life
- Industrial grade touch screen, one button operation, intuitive operating interface, remote upgrade & maintenance
- Chinese and English language operating system can meet different requirements of the users
- Automatic data storage, power failure memory to prevent data loss
- Up to 1200 test results can be stored
- Equipped with wireless micro-printer for convenient data printing (optional)
- Equipped with standard USB ports and professional software for convenient PC connection and data transfer (optional)

## **Test Principle**

The gas inside the test package is brought to the gas sensor by the air pump. The instrument analyzes the volume of oxygen and carbon dioxide (optional) contained in the sample gas by calculating the electrical signals generated by the gas sensor. When the preset condition is met, the test is completed and the system records the oxygen and carbon dioxide (optional) concentration.

 Labthink Instruments Co., Ltd.
 144 Wuyingshan Road, Jinan, P.R.China (250031)
 Phone: +86-531-85068566
 FAX: +86-531-85062108

 Labthink International, Inc.
 200 River's Edge Drive, Medford, MA, 02155, U.S.A.
 Phone: +1-617-830-2190
 FAX: +1-781-219-3638

# Labthink®

## Applications<sup>Note1</sup>

Basic Applications	Packaging Bags	Test the volume of $O_2$ and $CO_2$ (optional) in headspace of non-vacuum sealed packaging bags of coffee, cheese, milk tea, milk
		powder, bread, bean powder, instant food and drugs, etc.
	Packaging Containers	Test the volume of $O_2$ and $CO_2$ (optional) in headspace of
		packaging containers of coffee, milk powder, food, cheese, can,
		Tetra Pak and beverage, etc.
Extended Applications	Ampoule Bottles	Test the volume of $O_2$ and $CO_2$ (optional) in headspace of ampoule
		bottles

### **Technical Specifications**<sup>Note2</sup>

Specifications	C650B			
Testable Gases	O <sub>2</sub> (Standard)	CO <sub>2</sub> (optional)		
Test Principle	Electrochemistry	Infrared Absorption		
Sensor Service Life	2 Years (in air)	>15 Years		
Test Range	0 ~ 100%	0 ~ 100%		
Resolution	0.1%	0.01%		
Test Accuracy	±0.3%	$\pm$ (0.03% + displayed value * 5%)		
Sampling Volume	6 ~ 8 mL (Standard Mode)	15 mL (Standard Mode)		
Instrument Dimension	220mm (L) ×110mm(W) ×70mm(H)			
<b>Power Supply</b>	220VAC±10% 50Hz / 120VAC±10% 60Hz			
Net Weight	0.6 kg			

#### Configurations<sup>Note2</sup>

Standard Configurations	Instrument, Sampling Probe, Filter, Seal Gasket			
<b>Optional Parts</b>	Professional Software, Micro Printer, B2227 Test Frame for Headspace Gas			
	Analyzer, B2226 Underwater Sampling Set, CO <sub>2</sub> Sensor			

Note 1: The parameters in the table are measured by professional operator in Labthink laboratory according to relative requirements for laboratory standard conditions.

Note 2: The described product features, test standards and configurations should be in line with Technical Specifications.

#### Note 3: The picture in this brochure has included B2227 Test Frame for Headspace Gas Analyzer.

**Please Note:** Labthink is always dedicated to the innovation and improvement of product performance and function. Therefore, technical specifications are subject to change without further notice. Please visit our website at www.labthink.com for the latest updates. Labthink reserves the rights of final interpretation and revision.

Labthink Instruments Co., Ltd. 144 Wuyingshan Road, Jinan, P.R.China (250031) Phone: +86-531-85068566 FAX: +86-531-85062108 Labthink International, Inc. 200 River's Edge Drive, Medford, MA, 02155, U.S.A. Phone: +1-617-830-2190 FAX: +1-781-219-3638